

**PSS-2V1100, 2 Volt 1150 AH @ 100-hr. rate**  
**1070 AH @ 20-hr. rate**

**Rechargeable Sealed Lead Acid Solar Battery**



\*Case colour may vary depending on quantity


## Features

- Absorbent Glass Mat (AGM) technology for superior performance
- Valve regulated, spill proof construction allows safe operation in any position
- Superior cyclic performance
- Enhanced overcharge endurance
- Excellent recovery from over discharge situations
- Lower acid density, increased electrolyte volume and greater distance between the plates help keep the battery at lower temperatures and improve plate grid life
- Rugged impact resistant ABS case


## Terminals

(mm)

- T11: Threaded insert  
8 mm stud fastener



## Physical Dimensions: in (mm)




**L: 18.70(475) W: 6.89(175) H: 12.91(328) HT: 13.78(350)**

Tolerances are +/- 0.11 in. (+/- 3mm) for all dimensions. All data subject to change without notice.


## Performance Specifications

Nominal Voltage .....	2 volts
Nominal Capacity	
100-hr. (11.5A to 1.80 volts) .....	1150.0 AH
20-hr. (53.5A to 1.80 volts) .....	1070.0 AH
10-hr. (100.0A to 1.80 volts).....	1000.0 AH
5-hr. (175.7A to 1.75 volts) .....	878.5 AH
1-hr. (588.0A to 1.60 volts).....	588.0 AH
Max. Discharge Current.....	8000A (5s)
Approximate Weight .....	129.0 lbs. (59.0kg)
Internal Resistance (approx.) .....	0.45 milliohms
Shelf Life (% of nominal capacity at 68° F (20° C))	
1 Month .....	97%
3 Months .....	91%
6 Months .....	83%
Operating Temperature Range	
Charge.....	32° F (0° C) to 104° F (40° C)
Discharge.....	5° F (-15° C) to 122° F (50° C)
Storage.....	5° F (-15° C) to 104° F (40° C)
Case - 2V1100.....	ABS Plastic
Case - 2V1100FR .....	ABS Plastic (UL94 V-0 flame retardant)


### Discharge Characteristics



### Float Charging Characteristics




### Charge Mode



- A** With switch regulator (two-step controller) charge on curve max. Charge voltage for max 2hrs/day, then switch to continuous charge
- B** Standard charge without switching
- C** Boost charge (equalizing charge with external generator) charge on curve continuous charge for max. 5hrs/month, then switch over to standard charge

### Cycle Service Life



### Charging

**Cycle Applications:** Limit initial current to less than 300.0A. Charge until battery Voltage (under charge) reaches 2.40 to 2.50 volts at 77 °F (25 °C). Coefficient -5mV/°C


**“Float” or “Stand-By” Service:** Hold battery across constant voltage source of 2.25 to 2.3 volts at 77 °F (25 °C) continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition. Coefficient -3mV/°C

**Note:** Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged within 6 months of storage at 77 °F (25 °C) (shorter time frame at higher temp) otherwise permanent loss of capacity can occur.

### Chargers

Power-Sonic offers a wide range of chargers suitable for batteries up to 100AH. Please refer to the Charger Selection Guide in our specification sheets for “C-Series Switch Mode Chargers” and “Transformer Type A and F Series”. Please contact our Technical department for advice if you have difficulty in locating suitable models.

### Self-Discharge Characteristics



### Further Information

Please refer to our website [www.power-sonic.com](http://www.power-sonic.com) for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc.

